



## Breakaway Ratings

The following pressure ranges should be used as general guidelines only. They should not be interpreted to be absolute values. Actual breakaway may vary due to field dependent variables such as lubrication, contamination, etc.

|                 |   |                            |
|-----------------|---|----------------------------|
| Original Line®  | small bore (5/16" to 9/16")<br>larger bores (3/4" to 3")            | 7 to 10<br>psi 5 psi       |
| Double- Wall®   | MRS® Style<br>all others  | 15 to 17 psi<br>5 to 7 psi |
| PC Cylinders    | See Original Line®  |                            |
| Flat Series     | Varies by bore size<br>Please contact Bimba for further information |                            |
| Pneu-Turn®      |   | less than 5 psi            |
| Linear Thruster |   | 10 psi                     |
| Ultran® Slide   | Gold coupling<br>Silver coupling                                    | 25 psi<br>20 psi           |
| Ultran®         | Gold Coupling<br>Silver Coupling                                    | 20 psi<br>15 psi           |
| PFC             | Standard Models<br>Low Friction                                     | 10 psi<br>5 psi            |
| EF1             |   | 3 to 5 psi                 |

The information presented is in Bimba's best engineering opinion and should be used for reference only. Recommendations derived should be verified under actual operating conditions. Bimba reserves the right to change specifications without prior notice.

**Bimba Manufacturing Company**  
 Monee, IL 60449-0068  
 Telephone: 708.534.8544  
 Email: [cs@bimba.com](mailto:cs@bimba.com)  
[www.bimba.com](http://www.bimba.com)  
 Rev Level: 0

Leaders in Actuation.

To learn more about this product, scan this QR code with your mobile device.

