



## Breakaway Ratings

The following pressure ranges should be used as general guidelines only. They should not be interpreted to be absolute values. Actual breakaway may vary due to field dependent variables such as lubrication, contamination, etc.

Original Line®	small bore (5/16" to 9/16") larger bores (3/4" to 3")	7 to 10 psi 5 psi
Double- Wall®	MRS® Style all others	15 to 17 psi 5 to 7 psi
PC Cylinders	See Original Line®	
Flat Series	Varies by bore size Please contact Bimba for further information	
Pneu-Turn®		less than 5 psi
Linear Thruster		10 psi
Ultran® Slide	Gold coupling Silver coupling	25 psi 20 psi
Ultran®	Gold Coupling Silver Coupling	20 psi 15 psi
PFC	Standard Models Low Friction	10 psi 5 psi
EF1		3 to 5 psi

The information presented is in Bimba's best engineering opinion and should be used for reference only. Recommendations derived should be verified under actual operating conditions. Bimba reserves the right to change specifications without prior notice.

**Bimba Manufacturing Company**  
 Monee, IL 60449-0068  
 Telephone: 708.534.8544  
 Email: [cs@bimba.com](mailto:cs@bimba.com)  
[www.bimba.com](http://www.bimba.com)  
 Rev Level: 0

Leaders in Actuation.

To learn more about this product, scan this QR code with your mobile device.

